



Permanent Drain Pan Restoration Solution

Extend the life of your HVAC system with the trusted choice for over 20 years.

- Reduces downtime—ready to use in just hours.
- Reinforces structural integrity to prevent leaks.
- Creates a smooth, enamel surface for easy cleaning and optimal water drainage.



SELF-LEVELING | SMOOTH FINISH | CHEMICAL-RESISTANT

Experience the ease, savings, and durability of Pancrete – the ultimate choice for ensuring the longevity and efficiency of drain pans.



Why Choose Pancrete?

- Self-leveling and easy to apply.
- Offers permanent corrosion resistance.
- Mildew-resistant, anti-corrosive, and chemical-resistant.
- Minimizes downtime—cures in just hours.
- Strengthens structural integrity, stopping damaging leaks.
- Provides a smooth, enamel-like finish for easier cleaning and better drainage.

Pancrete: The Pan in a Can - Instructions

1. Clean and Prepare: Ensure the surface is ready.
2. Coat pan with V570 (optional-recommended)
3. Mix: Combine Pancrete Part A and B.
4. Pour: Pour in a new durable pan surface.
5. Dry: Allow 4–6 hours for curing.
6. Resume Service: Your unit is ready to go!

Please see full instructions before repairing pan. Visit our website or contact us at cs@cleanac.com for more information.

Part #	Makes	Coverage
PCQ	1 Quart	1.25 Sq ft
PC1	1 Gallon	5 Sq ft
PC2	2 Gallons	10 Sq ft
PC5	5 Gallons	25 Sq ft

Submersible and chemical-resistant. Strengthens and extends the life of your HVAC system. Prevents stagnant water and associated issues.