Frotect and Restore Metals Easy Roll on Coating

V570 fills fine cracks and pinholes while stopping corrosion. Originally designed for harsh HVAC environments, it's a durable, brush-on coating ideal for protecting any metal that isn't submerged in water.



PROTECTS | SMOOTH FINISH | STOPS CORROSION

V570 is tough, resilient, and perfect for extending the life of your metal assets.



Why Choose V570?

- Protects and refurbishes non-submersible metals.
- Seals cracks and pinholes up to 25 mils in diameter.
- Stands up to rust and corrosion in harsh conditions.
- Covers up to 200 square feet per gallon.
- Easy to clean, smooth finish
- Cost-Effective: Refurbish instead of replacing metal surfaces.
- Durable Protection: Stops rust and corrosion, saving your assets.
- Enhanced Longevity: V570s tough, cleanable surface extends life of metals.
- Versatile: Works on HVAC units, condensate drain pans, and more.

V570 Application Process

- 1. **Prepare:** Shut down the system, clean the surface thoroughly by removing dirt, rust, and grease using Clean Bond, and ensure it's completely dry.
- 2. **Mix:** Combine Part A and Part B by transferring between containers 20 times to ensure uniformity.
- 3. **Apply:** Use a roller or brush to coat vertical, slanted, or uneven surfaces. Avoid coating removable parts like screws or bolts.
- 4. **Cure:** Allow 6–8 hours to cure at 75°F. Start application immediately after mixing, as the product sets in 30 minutes.

Note: See full instructions before use to ensure optimal results.

For Drain Pan Applications

- Protect condensate drain pans with V570, followed by a ¼" layer of Pancrete for ultimate restoration.
- Prevent rust stains and other imperfections from showing through translucent coatings.

Coverage: 1 gallon covers approximately 200 square feet.

For over 20 years, V570 has been the go-to choice for professionals. Seal, protect, and restore your investments today!

